

1. Identification

Product Identification

Product Identifier: SET-3G
Recommended Use: SET-3G is an epoxy adhesive.
Use Restrictions: To ensure proper installation, use according to package directions. Complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
 Pleasanton, CA 94588
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada)
 1-352-323-3500 (International)

For most current SDS, please visit our website at www.strongtie.com/sds

2. Hazard Identification

General Information

SET-3G is a two component (1:1) system packaged as a single unit in a dual cartridge. The two parts of this product have been individually assessed according to the Globally Harmonized System (GHS). The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. Exposure to individual components will only occur with improper use. The final cured product will be uniformly gray in color and can be considered nonhazardous. Some hazards may apply upon grinding or cutting through hardened product. This Safety Data Sheet covers the hazards and responses for the safe use of this product.

Resin (White Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Skin Corrosion/Irritation	Category 2	H315: Causes skin irritation
	Serious Eye Damage/Irritation	Category 2	H319: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Chronic Aquatic Hazard	Category 2	H411: Toxic to aquatic life with long lasting effects

Main Symptoms: Irritation of eyes and skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin.

GHS Label Elements



Contains: Resins
Signal Word: **WARNING!**
Hazard Statements: H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H317: May cause an allergic skin reaction.
 H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements:
Prevention: P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P261: Avoid breathing mist or vapor.
 P264: Wash thoroughly after handling.
 P272: Contaminated work clothing should not be allowed out of the workplace.

SET-3G
SAFETY DATA SHEET



Response:	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352:	IF ON SKIN: Wash with plenty of water.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364:	Take off contaminated clothing and wash before re-use.
Storage:	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P391:	Collect Spillage.
	P403:	Store in a well-ventilated place.
Disposal:	P405:	Store locked up.
	P501:	Dispose of contents/container in accordance with local regulations.

Supplemental Label Information: None known.

Hardener (Black Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns
	Serious Eye Damage/Irritation	Category 1	H318: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Not Classified.		

Main Symptoms: Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin.

GHS Label Elements



Contains:	Amines, Crystalline Silica (Quartz), Benzyl Alcohol		
Signal Word:	DANGER!		
Hazard Statements:	H314:	Causes severe skin burns and eye damage.	
	H318:	Causes serious eye damage.	
	H317:	May cause an allergic skin reaction.	
Precautionary Statements:			
Prevention:	P201:	Obtain special instructions before use.	
	P202:	Do not handle until all safety precautions have been read and understood.	
	P260:	Do not breathe dust, mist, or vapor.	
	P264:	Wash thoroughly after handling.	
	P272:	Contaminated work clothing must not be allowed out of the workplace.	
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.	
	Response:	P301+P330+P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
		P310:	Immediately call a POISON CENTER/doctor.
		P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	Storage:	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
P363:		Wash contaminated clothing before reuse.	
P305+P351+P338:		IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313:		If eye irritation persists: Get medical advice/attention.	
P403+P233:		Store in a well-ventilated place. Keep container tightly closed.	
	P405:	Store locked up.	

SET-3G

SAFETY DATA SHEET

Disposal: P501: Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

Hazards Not Otherwise Classified (HNOC)

The above hazards are for the uncured SET-3G. Upon full cure, an innocuous solid which does not present any immediate hazards is formed. Upon grinding or cutting through the cured product, the following hazards may apply. Ensure that good work practices, and the necessary precautionary measures, are taken to maintain safe use of the product.



Chronic Health

Health Hazard:	Carcinogenicity	Category 1A
OSHA Hazard:	STOT, Repeated Exposure	Category 1
	Combustible Dust	
Hazard Statement:	May cause cancer. Causes damage to organs (lungs) with prolonged and repeated exposure. Can form explosive air-dust mixtures, avoid creating dust.	
Precautionary Statement:	Do not breathe dust. Do not allow dust to build up on surfaces.	

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classification: Global Harmonized System Classifications

The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

Resin (White Side)

Chemical Name	Weight %	CAS Number	EC Number
Phenolic Novolac Resin	50-70	28064-14-4	608-164-0
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, Aquatic Chronic 2: H411			
Bisphenol-A Based Epoxy Resin	30-50	25068-38-6	500-033-5
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, Aquatic Chronic 2: H411			
Neopentyl Glycol Diglycidyl Ether	1-5	17557-23-2	241-536-7
Classifications: Skin Irrit. 2: H315, Skin Sens. 1: H317			
Titanium Dioxide	1-5	13463-67-7	614-122-2
Classifications: Carc. 2: H351			

Hardener (Black Side)

Chemical Name	Weight %	CAS Number	EC Number
Crystalline Silica, Quartz	10-30	14808-60-7	238-878-4
Classifications: Carc. 1A: H350, STOT RE 1: H372			
Benzene-1,3-Dimethanamine	1-10	1477-55-0	216-032-5
Classifications: Acute Tox. 4: H302+H332, Skin Corr. 1: H314, Eye Corr. 1: H318, Skin Sens. 1: H317, Aquatic 3: H402+H412			
Benzyl Alcohol	1-10	100-51-6	202-859-9
Classifications: Acute Tox. 4: H302+H332			
Aliphatic Amines	1-5	N/A	N/A
Classifications: Acute Tox. 4: H302+H332, Skin Corr. 1: H314, Eye Corr. 1: H318, Skin Sens. 1: H317			
2,4,6-tris-(dimethylaminomethyl)phenol	1-5	90-72-2	202-013-9
Classifications: Acute Tox. 4: H302, Skin Irrit. 2: H315, Eye Irrit. 2: H319			

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

Eye Contact:	Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, consult a physician immediately.
Skin Contact:	Remove contaminated clothing and product, immediately wash affected area with soap and water. Chemical burns must be treated by a physician.
Ingestion:	Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. Consult a physician immediately.
Inhalation:	Remove patient to fresh air. Give oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, consult a physician.

Most Important Symptoms

Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. Permanent eye damage, including blindness, may result. Rash/dermatitis.

5. Fire-Fighting Measures

Suitable Extinguishing Media:	Extinguish with foam, carbon dioxide, dry powder, or water fog.
Additional Information:	None known.
Hazards during Fire-Fighting:	Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C). Irritating and toxic gases/fumes may be released during a fire. Water run-off can cause environmental damage.
Fire-Fighting Procedures:	Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Non-emergency personnel: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

Small spills (uncured):	Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.
Large spills (uncured):	Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water.
Cured Material:	Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Do not breathe dust, mist, or vapor. Use only in well-ventilated places. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Storage

Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a dry place out of direct sunlight. Keep out of the reach of children. Keep away from heat and sources of ignition. Store in a well-ventilated place. Store locked up.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

Protective Measure: Wear appropriate personal protective equipment.
Eye Protection: Wear chemical splash goggles or safety glasses with side shield.
Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection: Wear long sleeve shirt/long pants and other clothing as required to minimize contact.
Respirator Protection: The use of a respirator is not required during normal use of this product. If grinding or cutting cured product the use of an approved respirator is recommended.
General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

Mechanical ventilation or local exhaust ventilation is recommended, ventilation rates should be matched to conditions to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and emergency shower.

Exposure Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Titanium Dioxide (CAS 13463-67-7)	15 mg/m ³ (TWA)	10 mg/m ³ (TWA)	N/E
Benzene-1,3-Dimethaneamine* (CAS 1477-55-0)	0.1 mg/m ³ (ceiling)	0.1 mg/m ³ (ceiling)	0.1 mg/m ³ (ceiling)
Benzyl Alcohol (CAS 100-51-6)	5 mg/m ³ (TWA)	N/E	5 mg/m ³ (STEL)
Aliphatic Amines	0.1 mg/m ³ (ceiling)	0.1 mg/m ³ (ceiling)	0.1 mg/m ³ (ceiling)
Quartz (CAS 14808-60-7)	$\frac{10}{\%SiO_2 + 2} \text{ mg/m}^3$	0.025 mg/m ³ (respirable)	0.05 mg/m ³ (respirable)

*Skin Designation: Material can be absorbed through the skin.

9. Physical and Chemical Properties

Property	Resin	Hardener
Physical State:	Paste	Paste
Color:	White	Black
Odor:	Sweet	Ammoniacal
pH:	~7	~11
Flammability limit – lower %:	No data	No data
Flammability limit – upper %:	No data	No data
Vapor Pressure:	No data	No data
Vapor Density:	No data	No data
Solubility:	Insoluble in water	Slightly soluble in water
Freezing/Melting Point:	No data	No data
Boiling Point:	>300°F (>149°C)	>225°F (>107°C)
Flash Point:	256°F (124°C)	201°F (94°C)
Evaporation Rate:	No data	No data
Decomposition Temperature:	No data	No data
Specific Gravity:	1.215	1.863
VOC (after cure):	2 g/l	2 g/l
Kow:	No data	No data
Viscosity:	Non-Sag Gel	Non-Sag Gel

10. Stability and Reactivity

Resin (White Side)

Reactivity: This product is stable and non-reactive under normal conditions.
Chemical Stability: Stable under normal storage conditions.
Condition to Avoid: High heat and open flame.

SET-3G

SAFETY DATA SHEET

Substances to Avoid: Oxidizing agents, acids, organic bases, and amines.
Hazardous Reactions: Hazardous polymerization does not occur.
Decomposition Products: Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

Hardener (Black Side)

Reactivity: This product is stable and non-reactive under normal conditions.
Chemical Stability: Stable under normal storage conditions.
Condition to Avoid: High heat and open flame.
Substances to Avoid: Strong oxidizing agents. Strong acids.
Hazardous Reactions: Hazardous polymerization does not occur.
Decomposition Products: Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

11. Toxicological Information**Likely Routes of Exposure**

Ingestion: Corrosive material; causes severe irritation or burns to the gastrointestinal tract or respiratory tract if swallowed.
Inhalation: This material is a viscous liquid to semi-solid which does not easily form vapors. Do not inhale processing dust.
Skin contact: Causes severe skin burns. May cause an allergic skin reaction.
Eye contact: Causes serious eye damage.
Symptoms: Burns, redness, itching, tearing, swelling, and blurred vision. Rash/dermatitis. May cause severe irritation or burns to the gastrointestinal tract and respiratory system.

Information on Toxicological Effects**Acute Effects**

Toxicity: Occupational exposure to the substance or mixture may cause adverse effects.

Component	Estimate
SET-3G Resin Toxicity Estimate	Acute, Oral , LD50 > 3000 Acute, Dermal , LD50 > 2000
SET-3G Hardener Toxicity Estimate	Acute, Oral , LD50 > 2000

Component	Species	Test Result
Neopentyl Glycol Diglycidyl Ether (CAS 17557-23-2)	Rat	4500 mg/kg
Acute, Oral , LD50	Rat	> 2000 mg/kg
Acute, Dermal , LD50		
Phenolic Novolac Resin (CAS 28064-14-4)	Rat	> 2000 mg/kg
Acute, Oral , LD50	Rabbit	> 2000 mg/kg
Acute, Dermal , LD50		
Bisphenol-A Based Epoxy Resin (CAS 25068-38-6)	Rat	11400 mg/kg
Acute, Oral , LD50	Rabbit	2000 mg/kg
Acute, Dermal , LD50		
Titanium Dioxide (CAS 13463-67-7)	Rat	> 10000 mg/kg
Acute, Oral , LD50	Rat	> 6.82 mg/l
Acute, Inhalation , LC50		
Benzene-1,3-Dimethanamine (CAS 1477-55-0)	Rat	980 mg/kg
Acute, Oral , LD50	Rabbit	2000 mg/kg
Acute, Dermal , LD50	Rat	700 ppm, 1 hour
Acute, Inhalation , LC50		
Benzyl Alcohol (CAS 100-51-6)	Rat	1230 mg/kg
Acute, Oral , LD50	Rabbit	2000 mg/kg
Acute, Dermal , LD50	Rat	> 4.18 mg/l, 4 hours
Acute, Inhalation , LC50		
Aliphatic Amines	Rat	980 mg/kg
Acute, Oral , LD50	Rabbit	2000 mg/kg
Acute, Dermal , LD50		

SET-3G
SAFETY DATA SHEET



Component	Species	Test Result
2,4,6-tris-(dimethylaminemethyl)phenol (CAS 90-72-2)	Acute, Oral , LD50	Rat 1200 mg/kg
	Acute, Dermal , LD50	Rat 1280 mg/kg
Quartz (CAS 14808-60-7)	Acute, Oral , LD50	Rat 22500 mg/kg

Skin corrosion/irritation: Causes severe skin irritation and burns.
Eye damage/eye irritation: Causes serious eye irritation and damage.
Respiratory sensitization: No data available.
Skin sensitization: May cause an allergic skin reaction.
Aspiration hazard: Not expected to be an aspiration hazard.
**Specific target organ toxicity
 Single exposure:** No data available.

Chronic Effects

Germ cell mutagenicity: The available data does not indicate that any component of this product present at greater than 0.1% is genotoxic or mutagenic.
Carcinogenicity: May cause cancer. This product contains components which are considered carcinogens only in their respirable form. Due to the nature of this product, exposure to respirable particles is likely only when grinding or cutting cured product. Ensure good work practice and use of personal protective equipment as needed to control exposure.
Reproductive toxicity: No data available.
**Specific target organ toxicity
 Repeated exposure:** Causes damage to organs (lungs) through prolonged or repeated exposure to processing dust only. Repeated or prolonged exposure to respirable silica dust will cause lung damage in the form of silicosis. Symptoms include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Titanium Dioxide (CAS 13463-67-7)	1-5	2B	---	---	CA65
Quartz (CAS 14808-60-7)	10-30	1	KNOWN	A2	CA65

IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic
 NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen
 ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected
 CA65 – California Prop 65

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. SET-3G Resin is classified as toxic to aquatic life with long lasting effects. SET-3G Hardener is not classified as an environmental hazard. Avoid release to the environment.

Supporting Data

Component	Species	Test Result
Bisphenol-A Based Epoxy Resin (CAS 25068-38-6)	Aquatic , Fish, LC50	Salmo gairdneri 1.3 mg/l, 96 hours
	Aquatic , Crustacea, EC50	Daphnia magna 2.1 mg/l, 48 hours
	Aquatic , Algae, EC50	Algae > 11 mg/l, 72 hours

SET-3G
SAFETY DATA SHEET



Component	Species	Test Result
Benzene-1,3-Dimethanamine (CAS 1477-55-0)	Aquatic , Fish, LC50	Red killfish 87.6 mg/l, 96 hours
	Aquatic , Crustacea, EC50	Daphnia magna 15.2 mg/l, 48 hours
	Aquatic , Algae, EC50	Green algae 32.1 mg/l, 72 hours
Benzyl Alcohol (CAS 100-51-6)	Aquatic , Fish, LC50	Bluegill 10 mg/l, 96 hours
	Aquatic , Crustacea, EC50	Daphnia magna 55 mg/l, 24 hours
2,4,6-tris-(dimethylaminomethyl)phenol (CAS 90-72-2)	Aquatic , Fish, LC50	Cyprinus carpio 175 mg/l, 96 hours
	Aquatic , Algae, EC50	Green algae 84 mg/l, 72 hours

Persistence and degradability: This product is not expected to be readily biodegradable.
Bioaccumulative potential: No data available for this product.

Chemical	Log Kow	BCF	Bioaccumulation Potential
Phenolic Novolac Resin (CAS 28064-14-4)	3	---	low
BPA Based Epoxy Resin (CAS 25068-38-6)	2.64-3.78	3-31	low

Mobility in soil: This product is non-volatile.

Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Consideration

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Disposal of Cured Product: Chip or grind off surface. Solid material does not need special disposal consideration.

14. Transportation Information

	<u>Resin (White Side)</u>	<u>Hardener (Black Side)</u>
UN number:	UN3082	UN2735
UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant	AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-Dimethanamine), 8, III
Transportation Class:	9	8
Packing Group:	III	III
Environment Hazard:	Yes	No
Required Labels:	9	8
ERG Code (IATA):	9L	8L
EmS (IMDG):	F-A, S-F	F-A, S-B

Additional Information

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:
 This substance/mixture is not intended to be transported in bulk

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4): Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:					
	Immediate	Delayed	Fire	Pressure	Reactivity
Resin	Yes	Yes	No	No	No
Hardener	Yes	Yes	No	No	No

SARA 302 Extremely hazardous substance: No

SARA 311/312 Hazardous chemical: Yes

SARA 313 (TRI reporting):

Chemical	CAS Number	% In Blend (approx.)
Aluminum Oxide	1344-28-1	< 1

US. California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or reproductive harm.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Titanium Dioxide (CAS 13463-67-7)	1-5	2B	---	---	CA 65 (Carcinogenic)
Quartz (CAS 14808-60-7)	10-30	1	KNOWN	A2	CA 65 (Carcinogenic)
Carbon Black (CAS 1333-86-4)	< 0.1	2B	---	---	CA 65 (Carcinogenic)

IARC: 1- Carcinogenic 2- Possibly carcinogenic 3 – Not classifiable as to carcinogenicity 4 – Probably not carcinogenic
 NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen
 ACGIH – A1 – Confirmed carcinogen A2 – Suspected carcinogen A3 – Animal carcinogen A4 – Not classified A5 – Not suspected
 CA65 – California Prop 65

US State Right-To-Know Lists

Chemical	Massachusetts RTK	New Jersey Work and Community RTK Act	Pennsylvania Worker and Community RTK Law	Maine CHC
Titanium Dioxide (CAS 13463-67-7)	Listed	Listed	Listed	
Benzene-1,3-Dimethanamine (CAS 1477-55-0)	Listed	Listed	Listed	
Benzyl Alcohol (CAS 100-51-6)	Listed		Listed	
Crystalline Silica, Quartz (CAS 14808-60-7)	Listed	Listed	Listed	Listed

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

SET-3G
SAFETY DATA SHEET



REACH Registered Substances			
Chemical	CAS Number	EC Number	Index Number
Neopentyl Glycol Diglycidyl Ether	17557-23-2	241-536-7	603-094-00-7
BPA Based Epoxy Resin	25068-38-6	500-033-5	603-074-00-8
Benzyl Alcohol	100-51-6	202-859-9	603-057-00-5
2,4,6-tris-(dimethylaminomethyl)phenol	90-72-2	202-013-9	603-069-00-0

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
China	All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)
Europe	All components of this product are included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.
Japan	All components in this product are listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	All components of this product are included on the Existing Chemicals List (ECL)
New Zealand	All components of this product are included on the New Zealand Inventory.
Philippines	One or more components in this product are not listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.


16. Other Information

Date Prepared or Revised: September 2016
Supersedes: ---

Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com.

Additional Resin (White Side) Classifications

NFPA Ratings




HMIS Rating

HEALTH	2	PHYSICAL	0
FLAMMABILITY	1	PPE	B

Additional Hardener (Black Side) Classifications

NFPA Ratings



HMIS Rating

HEALTH	3	PHYSICAL	0
FLAMMABILITY	1	PPE	B

Abbreviations

ACGIH: American Conference of Governmental Industrial Hygienists
CAS No.: Chemical Abstract Service Registry Number

SET-3G
SAFETY DATA SHEET

CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HPR:	Hazardous Product Regulations (Canada)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Full Text of H – Phrases Under Section 3

H302:	Harmful if swallowed.
H314:	Causes severe skin burns and eye damage.
H315:	Causes skin irritation.
H317:	May cause an allergic skin reaction.
H318:	Causes serious eye damage.
H319:	Causes serious eye irritation.
H332:	Harmful if inhaled.
H350:	May cause cancer.
H351:	Suspected of causing cancer.
H372:	Causes damage to organs through prolonged and repeated exposure.
H402:	Harmful to aquatic life.
H411:	Toxic to aquatic life with long lasting effects.
H412:	Harmful to aquatic life with long lasting effects.

Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2016 Simpson Strong-Tie Company Inc.

Internal**FOR INTERNAL USE ONLY**

SET-3G Resin:	SET-3G Hardener:
XCOM3B – 50% Cartridge	XCOM3B – 50% Cartridge
	XCORR – 50% Cartridge